DGM8208SVGAT







H.265



Human / Vehicle Dual Lights
Detection



Starlight



Active Deterrence



PoE



MIC & Speaker



WDR



MicroSD Card
Recording




Al-based 8MP H.265 Dome IP Camera with Dual Lights

O FEATURES

- Starlight visibility to offer clear & color images even at night
- Al-based human / vehicle detection supported to avoid false detection alarms
- Dual lights (IR / warm light LED) mechanism to smartly switch images from B/W to color even at night when any motion is detected
- Siren triggered automatically when intruders are detected to deter intruders
- MicroSD card support (up to 256GB) for video storage
- ONVIF standard supported to simplify system integration
- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- Microphone & speaker built-in for audio transmission
- WDR to increase image recognizability in overexposure and dark areas
- Remote Surveillance
 Compatible with Internet Explorer 6 and above, Microsoft Edge & Google Chrome

O DIMENSIONS



Dimensional tolerance: ± 5mm



O SPECIFICATIONS

Image Sensor		1/2.8" SONY CMOS
Max. Resolution		3840 x 2160
Lens		f2.8mm / F1.6
Viewing Angle		112° (Diagonal)
Min Illumination		0.001 Lux (LED off), 0 Lux (LED on)
Shutter Speed		AUTO, 1/25s ~ 1/100000s
IR LED		2 dual light (IR & warm) units
IR Effective Distance		Up to 30 meters
Day / Night		YES
WDR Mode		YES (120dB)
RTC (real-time clock)		YES
MicroSD Card Slot		YES (up to 256GB)
Video		
Compression		H265 / H.264
Video Resolution	Main Stream	8MP (3840x2160) / 6MP (3072x2048) / 5MP (2592x1944) / 4MP (2560x1440) / 3MP (2304x1296) / 2MP (1080P) / 720P
	Sub Stream	2MP (1080P) / 720P / 720x480 / VGA / 640x360 / 480x360 / CIF
Frame Rate		4K (8MP) @ 20FPS
Video Profile		High profile / Main profile / Base profile
Multiple Video Streaming		3 streams
Bitrate Control		512Kbps - 12Mbps, VBR/CBR
Image Enhancement		WDR / BLC / HLC / 2D DNR / 3D DNR / AWB / MWB / AGC
Day / Night Switch		Auto / Color / (B/W) / Timing
Forced Anti-flicker		YES
Defog		YES
White Balance		Auto / Manual
Image Orientation		Rotate / Mirror
Privacy Mask		YES
Text Overlay		YES
OSD Title		Location / font size / text configurable; text input (English & Chinese characters) and ima upload (BMP) supported
Audio		
Microphone built-in		YES
Speaker built-in		YES
Encoding		G.711-u / G.711-a
Audio Adjustment		YES
Alarm & Event		
Detection Mode		Motion / Human / Vehicle Detection
Detection Schedule		YES
Motion Detection Area		1x1, 2x2, 3x2, 3x3, 4x3, 4x4, 8x8, 16x16, 22x18
Detection Alert		Audio alert with customized mp3 audio file(s)



• SPECIFICATIONS (CONTINUED)

Storage	
On-Board Storage	Built-in memory card slot, supports microSD / SDHC / SDXC card up to 256GB
Overwrite	YES
Maximum Recoding Time / per File	1, 2, 3, 5, 10, 20 & 30 minutes configurable
Recording Schedule	YES
Network	
LAN Port	RJ45 connector x 1 / 4KV lightning-proof
LAN Speed	100Mbps Based-T Ethernet
Supported Protocols	HTTP / RTSP / FTP / SMTP / DHCP / NTP / NFS / RTMP
ONVIF Compatible	Onvif 17.06 compatible
Number of Online Users	6
Remote Access	Internet Explorer 6 and above (recommended), Microsoft Edge & Google Chrome
General	
Web Interfede Language	
vveb interface Language	English, Traditional Chinese, Simplified Chinese, Russian, German, Italian, Turkish, Kore
	English, Traditional Chinese, Simplified Chinese, Russian, German, Italian, Turkish, Kore -30°C ~60°C
Operating Temperature	
Operating Temperature Operating Humidity	-30℃ ~60℃
Operating Temperature Operating Humidity POE	-30°C ~ 60°C 10%-90%RH
Operating Temperature Operating Humidity POE Power Source (±10%)	-30°C ~ 60°C 10%-90%RH IEEE 802.3af
Operating Temperature Operating Humidity POE Power Source (±10%) Power Consumption (±10%)	-30°C ~ 60°C 10%-90%RH IEEE 802.3af PoE / DC12V
Operating Temperature Operating Humidity POE Power Source (±10%) Power Consumption (±10%) Net Weight (g)	-30°C ~ 60°C 10%-90%RH IEEE 802.3af PoE / DC12V < 8 W
Web Interface Language Operating Temperature Operating Humidity POE Power Source (±10%) Power Consumption (±10%) Net Weight (g) Casing Optional Bracket / Junction Box	-30°C ~ 60°C 10%-90%RH IEEE 802.3af PoE / DC12V < 8 W 491

.*The specifications are subject to change without notice.