

## R380



### **Features**

- Diameter 380mm
- Modern, stylish and Innovative design
- Uniform light output
- Durable with life span over 50,000 hours
- 5 Years Guarantee
- Versatile installation, Recessed/ Suspension/ Surface Mounted
- Simple and convenient installation

### **Applications**

Meets the general and decoration lighting environment such as:

- Offices
- Restaurants
- Hotels
- Shops
- Schools and Hospitals
- Hallway & lobbies
- Meeting Rooms















## **REV 1.1** 04/25/2017

## Sheenly LED Round Panel Light

Sheenly LED Round Panel Light adopts qualified super bright LED as light source, which is stable, long life and no UV & IR emission. The anodized aluminum frame is stylish and fashionable with everlasting color. It is powered by low voltage constant current driver, which is safety, energy saving and long life.

Brand new round panel light R380, which is design with elegant appearance and versatile installation, combines three kinds of installation by the intelligent arrangement of its accessories. R380 creates extremely harmonies and uniform lights and provides an exciting effect.

### **Specifications**

Dimension	D380*13.5 mm
Power & Lumen Output	
18W	1800 lm @4000K
25W	2500 lm @ 4000K

#### **Color Temperature**

Color Rendering Index	>80
Pure White	$5700 \pm 350K$
Day White	$5000 \pm 300K$
Natural White	$4000 \pm 250K$
Warm White	$3000 \pm 200K$

Rated Life (L70) 50,000 Hours Housing Aluminum Optics **PMMA Beam Spread** 120°

**Operating Temperature** -10°C to +40°C (Amb.) Input Voltage 100-277/220-240V/AC

**Power Factor** >0.9

**Working Voltage** 


24 V/DC±2 18W 25W 36 V/DC±3 ΙP


**IP20** 

Installation Recessed Suspension

Surface Mounted

# **Dimension and Illumination Diagram**





Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

## **Ordering Information**

Sheenly	Class	Watt	сст	Model	Finishing	Options		
<b>SL</b> =Sheenly	PAN=Panel	18W	<b>WW</b> =3000 ±200K	R40	White			
Lighting		25W	<b>NW</b> =4000 ±250K					
			<b>DW</b> =5000 ±300K					
			<b>PW</b> =5700 ±350K					
	1	1		l	1	I		

Part Number	Power	сст	Lumen Output	Beam	Dimension
SL-PAN-18W-WW-R40	18W	3000 ±200K	1800		
SL-PAN-18W-NW-R40		4000 ±250K	2000		
SL-PAN-18W-DW-R40		5000 ±300K	2100		
SL-PAN-18W-PW-R40		5700 ±350K	2150	120°	D380*13.5 mm
SL-PAN-25W-WW-R40	25W	3000 ±200K	2300	120	D300 13.3 IIIII
SL-PAN-25W-NW-R40		4000 ±250K	2500		
SL-PAN-25W-DW-R40		5000 ±300K	2600		
SL-PAN-25W-PW-R40		5700 ±350K	2650		

#### Accessory



Suspension Kit:

R380 Surface mounted kit

Suspension kit

#### Shanghai Sheenly Lighting Co., Ltd.

No. 2755 SanLu Road, Minhang District Shanghai 201112, China Tel: (+86)-21-6411 3138 Fax: (+86)-21-6411 3862

\*All specifications subject to change without notice.

©2009-2017 Sheenly Lighting all rights reserved.