

SL-PAN-20W-XW-AN

Sheenly 300*300 LED Panel Light



Features

- 20W to replace 200W incandescent bulb
- 80% energy saving which means 80% CO₂ reduction
- No UV or IR emissions
- Durable with life span over 50,000 hours
- Environmentally friendly - fully recyclable, no mercury or other hazardous materials
- Simple and convenient installation
- Dimmable

Applications

Meets the general and decoration lighting environment such as:

- Office Lighting
- Restaurants
- Hotels
- Subway Stations
- School and Hospital
- Hallway & lobbies
- Meeting Rooms



REV 2.1

02/11/2010

Sheenly Ultra Slim LED Panel Light



Sheenly Ultra Slim LED Panel Light adopts qualified super bright LED as light source, which is stable, long life and no UV & IR emission. The anodized aluminum frame is stylish and fashionable with everlasting color. It is powered by low voltage constant current driver, which is safety, energy saving and long life.

Sheenly LED Panel light is the ideal replacement for traditional grid lights and fluorescent tubes. Moreover, Sheenly Panel light creates extremely harmonies and uniform lights, which conventional light never achieved.

Specifications

Dimension	298*298*12 mm
Lumen Output	
Warm white	1120 lm
Pure white	1460 lm
Equivalent Source Power	200 W incandescent lamp
Consumption	
Warm White	20 Watts
Pure White	20 Watts
Efficacy	
Warm White	56 (lm/w)
Pure White	73 (lm/w)
Color Temperature	
Warm White	3000-3300K
Pure White	5700-6000K
Color Rendering Index (CRI)	
Warm White	80
Pure White	80
Rated Life	Over 50,000 Hours
Housing	Anodized Aluminum
Beam Spread	
Warm White	120°
Pure White	120°
Operating Temperature	-40°C to +40°C (Amb.)
Input Voltage	100-240V/AC
Working Voltage	22.5 V/DC
Net Weight	1200g

Dimension



Cautions



- Indoor use only
- Do not open - no user serviceable parts inside

Ordering Information

Part Number	Dimension (mm)	LED Quantity	Color Temperature (K)	Protection	Voltage (V)	Lumen Output (lm)	Beam Spread	Power Consumption (Watt)
SL-PAN-20W-WW-AN	297.5*297.5*12	288	3000-3500 (WW)	IP20	100-240	1120	120°	20
SL-PAN-20W-PW-AN	297.5*297.5*12	288	5700-6000 (PW)	IP20	100-240	1460	120°	20

Rated Life

- 50,000 hours (70% lumen maintenance at Ta = 25°C)



Sheenly Lighting Co., Ltd.
 No. 88 Zhuyuan Road, Minhang District
 Shanghai 201112, China
 Tel: (+86)-21-6411 3138
 Fax: (+86)-21-6411 3138 - 632

*All specifications subject to change without notice.

©2009 Sheenly Lighting all rights reserved.